

Industrial Strength • Multi-Purpose • Cleans & Deodorizes

Concentrated Alkaling Degreaser & Gleaner

DESCRIPTION

HB-50 is a maximum strength alkaline degreaser and cleaner. It easily penetrates and removes fats, oils, waxes and greases from a wide variety of surfaces. HB-50 can be used in a variety of applications including; mop & bucket, manual sprayers, pump-up sprayers, steam cleaner and pressure washers. It is highly economical in use dilution and non-flammable. HB-50 is recommended for a variety of surfaces and applications, from heavily soiled industrial machinery to lightly soiled cleaning jobs.

DIRECTIONS

For routine maintenance: Mix 1 part concentrate to 100 parts water.

For general cleaning requirements: Dilute HB-50 between 1:30 and 1:50 with water and spray directly on soiled area, and agitate as necessary. Rinse or wipe off.

For heavy duty degreasing: Dilute HB-50 1:10 with water and spray directly on soiled area and agitate as necessary.

For pressure washing: Use HB-50 at a dilution ration of 1:5 to 1:10 with water. Rinse or wipe off.

Note: Do not use undiluted on composite floors, water base painted surfaces or aluminum.

RECOMMENDED APPLICATIONS

Tire Cleaning Garbage Containers Pressure Washing Asphalt Pavements Parts Washing / Degreasing Waste Receptacles Steam Cleaning Floor Finish Stripping

Machinery Cleaning Oil Spills Concrete Pads Floors & Floor Drains

ADVANTAGES

- High Alkaline, Caustic Formula Easily Penetrates & Removes Greases & Oils
- Multi-Purpose Product Designed for Many Applications
- Non-Toxic and Non-Flammable
- Industrial Strength Concentrate
- Low VOC's

TYPICAL PRODUCT SPECIFICATIONS

Appearance	· Yellow-Green Liquid
Scent	- Butyl
рН	-13.5
Weight, per U.S. gallon	-9.1 lbs.
Specific gravity	· 1.09
Viscosity	-Thin
Foam	- Moderate
Flashpoint	-None
Emulsification	- Excellent
Rinsability	- Excellent
Stability	- Excellent
Solubility	-Complete
DOT shipping	- Corrosive

